



# Cargo trailer assembling instruction

INac008\_UK\_B4-0008



All parts in the carton

- frame body 1pc
- 16" wheel 2pcs
- quick release 2 sets
- front and back panel 2pcs

**WARNING:**immediately discard all plastic bags and plastic wrapping materials!



Step one:  
Pull up the side frames,make them upward,locate and insert front/back panels into the bracket,fix the panels with safety pin.  
make sure the safety pin is locked.



Step two:release the tow bar safety pin, make the tow bar forward,insert the safety pin and make sure it is locked strongly.

Before assembling the wheels into the trailer, we'd like to introduce you the previous work.



wheel and quick release



Remove the conical nut from the QR lever take out one conical spring and hub safety washer

### Step three:how to assembling the wheel



A. put the wheel into the frame as picture



B. insert the quick release into the wheel axle



C. on the opposite side put the conical spring firstly,then put on the hub safety washer,screw the conical nut in a clockwise direction onto the QR lever and secure it with the spring and safety washer.



D. Make the both side of the hub safety washers hanging in the holes of the brackets. tighten the quick release.

**WARNING:**wheels must be properly installed.If wheels are not properly locked into the bracked and securing levers axes do not firmly in place the wheels could fall.Consult a specialist cycle if you have any doubt before use.



Step four:  
Rotating the red reflector bracket toward back,should be in the position as picture

### Step five;conneting the trailer to the bike



bike with axle



bike with QR



### IMPORTANT SAFETY INFORMATION

Failure to follow these warnings and assembling instructions could result in serious injury or death!  
Immediately discard all plastic bags and plastic wrapping materials.  
Maximum weight capacity for trailer is 50KGS.  
Never use this trailer if it becomes damaged!  
Never allow children to assembling, fold or disassembling this unit  
Accessories or parcels placed incorrectly in trailer may cause it to become unstable!Secure the load.  
Not for use with children

Before riding,check all parts are correctly asseled according to the factory's instructions.

Tires should be inflated to 25-30PSI for maximum control.Check tire pressure before each use.  
Use a foot pump or hand pump to inflate tires.pressurized air hoses can cause over inflation.  
Periodically re-check all fasteners to makesure they are tight.

### SAFE TOWING TIPS

Make sure your bike brakes work properly.Braking distance is increased when pulling a trailer.  
This trailer is wide.Allow extra clearance near curbs, signs,parked cars,and other obstacles  
A bicycle with trailer attached requires a wide turning radius.Do not urn sharply.  
Do not ride over curbs.Avoid bumps and holes.Always signal your turns.  
Use extra caution when turning on uneven pavement,and going downhill.  
Not for use at high speeds.do ot exceed 10MPH!  
Do not pull this trailer at night.